

TPR8NC



SAE 100 R8 / ISO 3949.2

NON CONDUCTIVE

Construction

Thermoplastic polyester inner tube
Two layers of aramid fibers braid
Pin pricked anti-abrasion polyurethane cover

Recommended fluid

Suitable for use with mineral oil, biological oil, polyglycol base oils, water-oil emulsion and water.

Temperature range

Hydraulic oils: -40°C to +100°C (-40°F to +212°F)
Polyglycol base oils, water-oil emulsion and water:
up to +85°C (+ 185°F)

HOSE TYPE	Internal diameter			External diameter	Min. bend radius	Max. Working pressure		Min. Burst pressure		Weight
	Size	Inch	DN	mm	mm	Bar	Psi	Bar	Psi	Kg/m
TPR8NC-02	-2	1/8"	4	8,3	15	362	5249	1450	21025	0,05
TPR8NC-03	-3	3/16"	5	9,3	22	362	5249	1450	21025	0,06
TPR8NC-04	-4	1/4"	6	11,8	30	362	5249	1450	21025	0,11
TPR8NC-05	-5	5/16"	8	14,2	40	350	5075	1400	20300	0,13
TPR8NC-06	-6	3/8"	10	16,0	70	300	4350	1200	17400	0,15
TPR8NC-08	-8	1/2"	12	20,5	90	250	3625	1000	14500	0,23
TPR8NC-10	-10	5/8"	16	24,0	130	200	2900	800	11600	0,28
TPR8NC-12	-12	3/4"	19	27,5	150	162	2349	650	9425	0,34
TPR8NC-16	-16	1"	25	34,2	190	140	2030	560	8120	0,43

Size: hose internal diameter according to SAE J517

Inch: hose internal diameter in inches

DN: nominal internal diameter according to manufacturing prescription (EN)

1 bar = 14,503 pound per square inch (PSI)